



BYD MATERIAL/PRODUCT SAFETY DATA SHEET

1. Identification of the Substance or Preparation and Company

| | |
|----------------------------|--|
| Product | Nickel Metal Hydride cells and batterie |
| Manufacturer | BYD Company Limited |
| Production sites | Yan An Road, KuiChong, Longgang, Shenzhen, 518119, P.R.China Tel: 86-755-89888888 Fax: 86-755-89773959 |
| Emergency telephone number | Tel: 86-755-89888888 |

2. Composition & Information on Ingredients

| Ingredients | Content | CAS No. | Classification |
|---------------------|------------|------------|---|
| Nickel hydroxide | ≈25 -- 40% | 12054-48-7 | Carc. Cat. 3; R40 Xn; R20/22 R43 N; R50-53 |
| Metal Hydride Alloy | ≈25 -- 40% | | |
| Cobalt oxide | ≈3% | 1307-96-6 | Xn; R22 R43 N; R50-53 |
| Potassium hydroxide | ≈6% | 1310-58-3 | Xn; R22 C; R35 |
| Iron | ≈15~25% | 7439-89-6 | --- |

3. Hazards Identification

Do not short circuit, puncture, incinerate, crush, immerse, force discharge or expose to temperature above the declared operating temperature range of product. Risk of fire or explosion.

Under normal conditions of use, the electrode materials and liquid electrolyte they contain are not exposed to the outside, provided the battery integrity is maintained and seals remain intact.

Effects of Overexposure

Eye Effects: In the case of a fire or cell rupture the electrolyte solution inside battery is extremely corrosive to eye tissue and may result in permanent blindness. Contact with nickel oxide may cause minor irritation.

Skin Effect: Contact with electrolyte solution inside battery may cause serious burns to skin tissues. Contact with nickel compounds may cause result in chronic eczema or nickel itch.

Ingestion: Ingestion of electrolyte solution causes tissue damage to throat area and gastro/respiratory tract. Ingestion of nickel compounds causes nausea and intestinal disorders.

Inhalation: No exposure possible except in the case of fire or abuse. Effects of inhalation of nickel compounds vary from mild irritation of nasal mucous membranes to damage of lung tissues proper.

Approved By:

Anthony Tang

Date:

2015.1.6



4. First Aid measures

The information below refers to exposure to the ingredients.

Battery Electrolyte:

Eye Contact: Flush with plenty of water for at least 15 minutes if abuse causes safety vents to activate. Get immediate medical attention.

Skin Contact: Remove contaminated clothing and flush effected areas with plenty of water for at least 15 minutes. Wash with soap and water.

Ingestion: Do not induce vomiting. Dilute by giving water. If available give several glasses of mild. Get immediate medical attention. Do not give anything by mouth to an unconscious person. Call a physician or Poison Control Centre immediately

Inhalation: Remove to fresh air. Give oxygen or artificial respiration if needed. Get immediate medical attention.

Further treatment: Show this safety data sheet to the doctor in attendance.

5. Fire-fighting measures

Suitable extinguishing media

Dry powder, carbon dioxide (CO₂), sand.

Extinguishing media which must not be used for safety reasons

Water, water spray.

Specific hazards

Risk of receptacle bursting.

Special protective equipment for firefighters

In the event of fire, wear self contained breathing apparatus. Wear personal protective equipment.

Hazardous decomposition products

Nickel and cobalt compounds.

6. Accident release measures

The information below refers to exposure to the ingredients.

Personal precautions

Remove personnel from area until fumes dissipate. Use personal protective equipment. Avoid contact with skin and eyes.

Environmental precautions

Prevent further leakage or spillage if safe to do so.

Do not allow material to contaminate ground water system.

Methods for cleaning up

Pick up and transfer to properly labelled containers. Dispose of in accordance with local regulations.

Approved By:



Date:

2015.1.6



7. Handling and Storage

| | |
|----------|---|
| Handling | The cells and batteries manufactured from them may be highly charged and are capable of high-energy discharge. Care should be taken to handle cells properly to avoid shorting or misuse that will result in rapid uncontrolled electrical, chemical, or heat energy release. Do not short circuit. Do not dispart cell. Do not allow an exposed flame or spark to come near the cells. Do not mix new and used batteries. Keep batteries in non conductive trays. |
| Storage | The cells and batteries shall not be stored in high temperature, the maximum temperature is 60°C (less than one month), otherwise the cells and batteries maybe leakage. Besides, the cells and batteries shall be protected from short circuit and protected from movement that could result in short circuit. |
| Other | Follow manufacturer's recommendations regarding maximum recommended currents and operating temperature range. |

8. Exposure Controls & Personal Protection

| | |
|------------------------|---|
| Exposure Limit Values | Nickel hydroxide, 0.5mg(NI)/m3 TWA Potassium Hydroxide. 2mg/m3 MAC |
| Respiratory protection | Use NOISH/MSHA approved respirator if cell broken open during a fire to maintain exposure levels below the TWA for hydrogen absorbed alloy and nickel compounds. |
| Hand protection | If exposure to electrolyte solution, or dried salts is likely, use any water-insoluble non-performance glove, i.e., synthetic rubber. Do not use leather or wool. |
| Eye protection | Use splash goggles or face shield if cell activates due to abuse. |
| Other | Rubber apron or equivalent if exposure to electrolyte solution is likely. |


9. Physical and Chemical Properties

| | |
|--------------------|--|
| Appearance | Sealed battery |
| Odour | Odourless |
| Color | N/A |
| PH | N/A |
| Flash Point | N/A unless individual components exposed |
| Flammability | N/A unless individual components exposed |
| Rlatetive density | N/A unless individual components exposed |
| Solutbility(Water) | N/A unless individual components exposed |
| Aolubility(other) | N/A unless individual components exposed |

10. Stability and Reliability

| | |
|----------------------------------|---|
| Stability | Stable under normal conditions |
| Condition to avoid | Keep away from heat and sources of ignition |
| Material to avoid | Aluminum, zinc and other active metals, acid, chlorinated and aromatic hydrocarbons, nitro-carbons, halocarbons. Water. |
| Hazardous Polymerization | Hazardous Polymerization does not occur |
| Hazardous decomposition Products | Nickel oxide, and potassium hydroxide |

Approved By:



Date:

2015.1.6



11. Toxicological Information

| | |
|---|--|
| The information below refers to exposure to the ingredients | |
| Acute toxicity | Nickel hydroxide LD50/oral/rat = 1500mg/kg, potassium hydroxide LD50/oral/rat = 273mg/kg |
| Local effects | Causes severe burns. Risk of serious damage to eyes. Harmful by inhalation and if swallowed. |
| Long term toxicity | No data available. Avoid repeated exposure. |
| Specific effects | May cause sensitization by inhalation and skin contact. Limited evidence of a carcinogenic effect. |

12. Ecological Information


| | |
|-------------------------------|--|
| Mobility | None known if used/disposed of correctly |
| Persistence and degradability | None known if used/disposed of correctly |
| Ecotoxicity effects | None known if used/disposed of correctly |

13. Disposal Considerations

| | |
|---------------------------------------|--|
| Waste from residues / unused products | The battery is a hazardous waste under RCRA. Dispose of in accordance with appropriate local regulations. Should not be released into the environment. |
| Contaminated packaging | Not applicable |

14. Transport Information

| | |
|---|-------------------|
| Transported by air: | |
| Not classified as dangerous goods in the meaning of air transport regulations. | |
| Regulatory body | Special provision |
| IATA(56 th Edition-2015) | A123 |
| International Civil Aviation Organization (ICAO) and International Air Transport Association(IATA), Special Provision A123 state: An electrical battery or battery powered device having the potential of dangerous evolutions of heat that is not prepared so as to prevent a short circuit(e.g. in the case of batteries, by the effective insulation of exposed terminals; or in the case of equipment, by disconnection of the battery and protection of exposed terminals) is forbidden from transportation. | |
| BYD sealed Nickel Metal Hydride batteries are not subject to these regulations and special provision as their terminals are protected from short-circuit when packaged for transport. | |
| Transported by sea: | |
| Classified as dangerous goods in the meaning of sea transport regulations. | |
| According to the meeting of Committee of Experts on the Transport of Dangerous Goods in Geneva, 29 November–7 December 2010, mainly discuss about the draft amendments to the Recommendations on the Transport of Dangerous Goods (Model Regulations and Manual of Tests and Criteria) adopted at the thirty-fifth, thirty-sixth and thirty-seventh sessions. The content includes that adding the Batteries, Nickel-Metal Hydride for transport of dangerous goods only when transported by sea. The hazardous level is the 9 th level and the UN number is UN3496. (Reference documents: ST/SG/AC.10/C.3/70, Annex and ST/SG/AC.10/C.3/74/Add.1.) | |
| Regulatory body | Special provision |
| IMDG(17 th Edition-2011) | 117 |
| SP 117 state: subject to these regulations only when transported by sea | |

Approved By:  Date: 2015.1.6



15. Regulatory Information

| | |
|---|---|
| The preparation is classified as dangerous in accordance with Directive 1999/45/EC. | |
| Symbol | C - Corrosive N - Dangerous for the environment |
| R-phrases | R35 - Causes severe burns. R40 - Limited evidence of a carcinogenic effect. R20/22 - Harmful by inhalation and if swallowed. R42/43 - May cause sensitization by inhalation and skin contact. R50/53 - Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. |
| S-phrases | S 1/2 - Keep locked up and out of the reach of children. S36/37/39 - Wear suitable protective clothing, gloves and eye/face protection. S45 - In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). S60 - This material and its container must be disposed of as hazardous waste. S61 - Avoid release to the environment. Refer to special instructions/safety data sheets. |

16. Other information

The data in this MSDS relates only to the specific material designed herein.

Date issued: 2004/06/20

Last Date Revised: 2015/01/06

Note: This information has been compiled from sources considered to be dependable and is accurate and reliable. It is the user's responsibility to satisfy himself as to the suitability and completeness of this information for his own particular use. We do not accept liability for any loss or damage that may occur, whether direct, indirect, incidental or consequential, from the use of this information nor do we offer warranty against patent infringement. Additional information is also available by contacting BYD.

Approved By:



Date:

2015.1.6